



PREZONE642

10-input mixer and 2-zone preamp

- 2 completely independent zones
 - 6 mic inputs and 4 line inputs
- Output level display for each zone and input
 - Back-up 24V power supply



SKU: H9902

Category: [Audio mixers](#)

FEATURES

- 6 mono mic/line inputs via XLR/mono jack
- Phantom power supply and talkover on inputs 1 and 2
 - 4 stereo inputs via RCA or jack
 - Priority input via 6.35mm jack
- Zone 1 and 2 balanced mono outputs via XLR
 - Zone insert via 6.35mm TRS jack
 - Balanced SUB output per zone via jack
 - REC stereo output via RCA
- Gain and tone settings (3 bands) on mic inputs
 - Gain settings on stereo inputs
 - Tone settings (2 bands) per zone
 - SUB volume settings per zone
- Screwdriver required to access technician-level settings

- Zone assignment and PFL on each channel strip
 - Signal and peak LED display
- Output level display for each zone via 8-LED VU metre
- Headphones output with volume control (zones and PFL)
 - Power supply: 230V 50/60Hz
 - Power consumption: 16 Watts
- Back-up power supply: DC 24V with Link Out
- Frequency response: 20Hz - 20kHz (+/- 3dB)
 - THD (1kHz rated power): < 0.2%
 - Equaliser:
 - High: +/-12dB @ 12.5kHz
 - Mid: +/-12dB @ 2.5kHz
 - Low: +/- 12dB @ 80Hz
- Dimensions: 295 x 85 x 482 mm
 - 19" rack-mountable
 - Height: 2 units
 - Weight: 5 kg

INSTRUCTION MANUALS

FR



EN



NL



DE



ES

